

Model Type	rpm		Santrüfuj Kuvveti Centrifugal Force				(*)Statik Moment Statical Moment		Ağırlık Weight		Giriş Gücü Input Power		Nominal Akım Nom. Current		I <sub>a</sub> / I <sub>n</sub>	
			( Kg/F )		( KN )		( Kgmm )		( Kg )		( W )		( A )			
	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	400V 50Hz	460V 60Hz	50Hz	60Hz
CPV 20/10	1000	1200	2064	2000	20,24	19,62	1847,0	1242,6	130	117	1700	2100	3,50	4,15	5,50	5,50
CVP 20/15	1500	1800	2568	2520	2519	24,72	1021,0	695,8	112	112	2200	2400	3,40	4,00	7,30	7,30
CPV 30/15	1500	1800	3150	3142	30,90	30,82	1252,4	867,5	116	116	2200	2400	3,40	4,00	7,30	7,30
CPV 20/3	3000	3600	2368	2346	23,23	23,01	235,4	161,9	94	92,5	3300	4000	5,90	7,00	5,10	5,10
CPV 25/3	3000	3600	2555	2507	25,06	24,59	254,0	173,1	95	93,5	3300	4000	5,90	7,00	5,10	5,10
CVP 30/3	3000	3600	3008	2907	29,5	28,52	200,7	204,82	96,5	94,5	3300	4000	5,90	7,00	5,10	5,10

(\*) Working moment = 2x static moment

Gövde Ölçüleri - Overall Dimensions (mm)

Model Type	A	G
CPV 20/10 (50Hz)	559	147
CPV 20/10 (60Hz)	489	112
CVP 20/15	489	112
CPV 30/15	489	112
CPV 20/3	400	67
CPV 25/3	400	67
CVP 30/3	400	67

