


MT 70x400-550-650-800

Gövde Ölçüler - Overall Dimensions (mm)

Model Type	IEC				NEMA			A	B	C	ØD	E	F	X	Y	Ağırlık Weight (Kg)
	Motor Boyutu Motor Type	P (KW)			Motor Boyutu Motor Type	P (HP)										
		3000 rpm	1500 rpm	1000 rpm		1800 rpm	1200 rpm									
MT 70x400	250M	55	55	37	404T	100	60	406	330	325	24	585,5	80	510	410	136,5
MT 70x550	280S	75	75	45	405T	100-125	75	457	368	475	24	735,5	80	560	500	155,0
	280M	90	90	55	444T	125-150	100		419							
MT 70x650	315S	110	110	75	445T	150-200	125-150	508	406	575	28	835,5	80	570	630	172,0
MT 70x800	315M	132-160	132-160	90-110	447T	200-250	150-200		457	695	24	955,5	80	750	630	191,0
	315L	160-200	160-200	110-160	449T	200-250	200-300	508								



- En verimli germe ve montaj mesafesi
Most efficient tensioning and installation distance
- Verimli germe ve montaj mesafesi
Efficient tensioning and installation distance
- Tavsiye edilmeyen germe ve montaj mesafesi
Non-recommended tensioning and installation distance