



ES-L 16...45

ES-L 50

### ES-L Serisi / Series

| Model Type  | M<br>Yükleme eksenini J z+z<br>load in J on axes z+z<br>[ N ] | A<br>Yüksüz<br>Unloaded | A<br>Max. Yük<br>Max. load | B  | C    | D   | E   | F | G | H    | I   | J     | L   | K<br>max | N   | O    | P  | Ağırlık<br>Weight<br>( Kg ) |
|-------------|---|-------------------------|----------------------------|----|------|-----|-----|---|---|------|-----|-------|-----|----------|-----|------|----|-----------------------------|
| ES-L 16     | 200 - 500   | 58                      | 45                         | 30 | 7    | 65  | 85  | 4 | 2 | 10   | 40  | 58,4  | 89  | 1,8      | 49  | -    | -  | 0,58                        |
| ES-L 18     | 450 - 1200  | 68                      | 53                         | 35 | 9,5  | 80  | 105 | 5 | 3 | 12,5 | 50  | 74    | 110 | 2,1      | 61  | -    | -  | 1,03                        |
| ES-L 25     | 750 - 2000  | 84                      | 65                         | 44 | 11,5 | 110 | 140 | 6 | 3 | 15   | 60  | 85,3  | 146 | 2,7      | 71  | -    | -  | 1,39                        |
| ES-L 35     | 1500 - 3500   | 113                     | 87                         | 60 | 14   | 140 | 175 | 6 | 4 | 17,5 | 80  | 116,4 | 181 | 3,6      | 98  | -    | -  | 3,19                        |
| ES-L 45     | 2000 - 5800   | 144                     | 111                        | 76 | 18   | 170 | 220 | 7 | 5 | 25   | 100 | 147,5 | 227 | 4,6      | 120 | -    | -  | 7,69                        |
| ES-L 50x120 | 4000 - 10000  | 172                     | 139                        | 80 | 18   | 185 | 235 | 8 | 6 | 25   | 120 | 162   | 243 | 10,4     | 142 | 13,5 | 90 | 10,38                       |
| ES-L 50x160 | 5000 - 15000  | 172                     | 139                        | 80 | 18   | 185 | 235 | 8 | 8 | 25   | 160 | 206   | 243 | 10,4     | 186 | 13,5 | 90 | 15,12                       |
| ES-L 50x200 | 7500 - 20000  | 172                     | 139                        | 80 | 18   | 185 | 235 | 8 | 8 | 25   | 200 | 246   | 243 | 10,4     | 226 | 13,5 | 90 | 18,21                       |

X ÷ X eksenindeki maksimum yük Z ÷ Z eksenindeki 2 katıdır. / The max. load on X ÷ X axes is the double value from Z ÷ Z axes.

Y ÷ Y eksenindeki maksimum yük Z ÷ Z eksenindeki %20'sidir. The max. load on Y ÷ Y axes is 20 % from Z ÷ Z axes.